

SS SEED STARTER ASSEMBLY

1. UNPACK ALL CARTONS AND BAG KITS. *COMPARE PARTS TO PARTS LIST ON OPPOSITE PAGE. YOU MAY WANT TO SAVE CARTONS FOR STORAGE OF UNIT WHEN NOT IN USE.*
2. LAY TWO OF THE BENT STEEL RODS **(R)** FLAT, (ONE ON TOP OF THE OTHER). SLIDE TWO **LONG CHAINS (C)** OVER THE ENDS AND AROUND BEND. **(REFER TO DETAIL DRAWING)**
3. SLIDE A PLASTIC CLAMP **(PC)** OVER EACH END. **(REFER TO DETAIL DRAWING)** POSITION THE CLAMPS JUST AROUND BEND. USE A SCREW **(S)** AND NUT **(N)** TO TIGHTEN CLAMPS. THIS WILL NOW BE THE TOP HALF OF THE UNIT.
4. USING ONE REMAINING BENT STEEL ROD **(R)** AND A **SHORT CHAIN (C)**. SLIDE THE LAST LINK OF THE CHAIN OVER THE END OF THE ROD AND AROUND BEND. NOW SLIP A STEEL TUBE **(T)** OVER THE END OF THE ROD. REPEAT THIS STEP ON OTHER END.
5. TAKE THE LAST BENT STEEL ROD **(R)**, AND SLIDE THE OPPOSITE ENDS OF THE CHAINS OVER AND AROUND BENDS, NOW SLIP THE REMAINING TUBES **(T)** ON. THIS WILL NOW BE THE BOTTOM HALF OF THE UNIT.
6. JOIN THE TOP AND BOTTOM BY SLIPPING THE ENDS OF THE TOP HALF INTO THE TUBES **(T)** OF THE BOTTOM HALF.
7. STAND UP THE "A" FRAME AND SPREAD THE BOTTOM APART.
8. INSTALL THE LAMPS INTO THE FIXTURE, BE SURE LAMPS ARE SEATED PROPERLY BY ROTATING THE NOTCH ON END OF LAMP. ONE NOTCH WILL BE VISIBLE, CENTERED DIRECTLY IN THE SOCKET OPENING.
9. HANG THE FIXTURE ON THE LONG CHAINS THROUGH T-SLOTS ON THE TOP OF THE FIXTURE.

ON UNITS WITH PLASTIC DOMES AND TIMER

SET THE TIMER FOR 16 TO 18 HOURS ON. WHEN THE SEED STARTER IS LOCATED IN A COOL AREA, YOU MAY WANT TO TURN ON THE LAMPS DURING THE COLDEST PART OF THE DAY.

NOTE; YOU WILL NOT USE THE INSTRUCTIONS THAT COME IN THE LIGHT FIXTURE BOX.

PARTS LIST

BAG KIT (inside the light fixture)

- 2 - 21" CHAINS (C) (USED ON LIGHT FIXTURE)
- 2 - PLASTIC RING CLAMPS (PC)
- 2 - SMALL SCREWS (S)
- 2 - SMALL HEX NUTS (N)

STAND PARTS

- 2 - 10" CHAINS (C) (USED ON FRAME)
- 4 - 23" STEEL TUBES (T) (inside fixture box)
- 4 - BENT STEEL RODS (R)
- 1 - 2 LAMP SHOPLITE
- 2 - GROW LAMPS

